

# SCM100ASL PRO: 3-way active\*



## Features

- 25mm soft dome tweeter.
- Full "SL" spec 12"/314mm bass driver.
- ATC 75mm "Super Dome" mid driver.
- On board ATC grounded plane 350W Tri-amplifier.
- LF contour control.
- Clip indication.
- 6 year warranty.

## Specifications

**Drivers :** HF 25mm, Mid 75mm, LF 314mm  
**Amplitude Linearity ( $\pm 2\text{dB}$ ) :** 65Hz-17kHz  
**Cut-off Frequencies (-6dB, free-standing) :** 32Hz, 22kHz  
**Horizontal Dispersion :**  $\pm 80^\circ$ , Coherent **Vertical Dispersion :**  $\pm 10^\circ$ , Coherent  
**Max. Continuous SPL (1 metre) :** 115dB  
**Crossover Frequencies :** 380Hz, 3.5kHz  
**Input Connectors :** Male XLR **Input Sensitivity :** 1V **Input Sensitivity Trim :**  $\pm 6\text{dB}$   
**Input Impedance :** Balanced  $> 10\text{k}\Omega$   
**Amplifier Output :** Bass 200W, Mid 100W, High 50W  
**Filters :** Even Order Critically Damped  
**Overload Protection :** Active FET momentary gain reduction plus thermal tweeter protection  
**Front Panel Indicators :** Power On indicator, Gain Reduction warning  
**LF EQ :** +6dB @ 40Hz  
**Dimensions (HxWxD) :** 832 x 398 x 581mm (32.8" x 15.7" x 22.9")  
Depth with amplifier at rear adds 3" **Weight :** 65kg / 143lbs

\*Passive versions available.

ATC reserves the right to vary products and specifications without prior notice.



### Loudspeaker Technology Ltd

Gypsy Lane, Aston Down, Stroud, Gloucestershire GL6 8HR United Kingdom

Telephone 01285 760561 Fax 01285 760683

Email [info@atc.gb.net](mailto:info@atc.gb.net) Website [www.atcloudspeakers.co.uk](http://www.atcloudspeakers.co.uk)