

CYRUS 6 DAC SPECIFICATION

RELEASED: 2013

- > Integrated amplifier with DAC
- > 40W per channel
- > Six analogue and five digital inputs

Multi Zone Playing

Zone 2 playing allows you to listen to two sources through the amplifier at the same time, so you can enjoy different music in different rooms.

Electrical

Inputs	6 analogue, 2 electrical SPDIF, 2 optical SPDIF, 1 USB (computer slave)
Outputs	Zone 2, preamp out, headphone, bi-wire loudspeakers
Power Supply	130VA transformer
Communications	MC-Bus™ System Bus

Specifications

Continuous Power	50W/CH into 4 Ohms 40W/CH into 8 Ohms
Distortion	0.003%, 1kHz into 8 Ohms
Frequency Response	-3 dB, 0.1Hz and 100kHz
Sensitivity (40W) Line	179mV
Input impedance	40kΩ (RCA).
Output voltage	200mV (Tape out), 380mV
S/N ratio	104dBA

In Comparison

Cyrus 6 DAC vs. Cyrus 8 DAC

The **Cyrus 8 DAC** has a more powerful 350VA transformer, producing 70W per channel. You can also improve the performance of the **Cyrus 8 DAC** by connecting a **PSX-R** to it.

