

## DAC XP SIGNATURE SPECIFICATION

RELEASED: 2013

- > Upsampling 32-bit/192kHz DAC with in-built preamplifier
- > Re-clocking circuit adjusts tolerance depending on source quality
- > Four 32-bit DACs and advanced circuitry create almost negligible interference and distortion

### Upsampling DAC

The intelligent DAC in the **DAC XP Signature** upsamples all digital inputs to 32-bit/192 kHz resolution.

### Signature series

After the success of our limited edition Anniversary System, Signature brings the advances made in fine-tuning that to our separates. It's the top range in the Cyrus catalogue, representing months of research, tuning and testing to produce the purest Cyrus sound yet.

### Electrical

Inputs	4 SPDIF, 2 TOSlink optical, 2 RCA
Outputs	4 XLR, 2 RCA
Power Supply	Dual 75VA toroidal transformers
Communications	MC-Bus™ System Bus

### Specifications

Digital Input	500mV pk-pk
Digital Output	500mV pk-pk
Sample rate range	32k – 192k
Sample rate tolerance	+/-100ppm of 32/44.1/48kHz and multiples to 192k
Unbalanced Output	2.3V//47Ω
Balanced Output	4.4V//47Ω
S/N ratio	115dBA
THD+N	0.002% (ref 0dBFS)
Dimensions	73 x 215 x 360 mm (H x W x D)
Weight	6.5kg

