

The compact bookshelf speaker: BS 52



diameters

- overload-protection provides trouble free operation: this loudspeaker is recommended for use with 20-100W/ch powerful amplifiers
- elegant design: all driver baskets and mounting plates of the 50 series are in the new colour *titan metallic*, specially designed for ELAC
- also designed for unobtrusive wall mounting and supplied with four transparent silicone hemispheres for decoupling to the wall

The smallest bookshelf speaker of the new 50 series is no bigger than a bookend. The BS 52 features balanced sound, elegant design and the best possible value for money.

Technical features

- 1 x 130 mm woofer with cellulose diaphragm and concave-shaped capton bobbin for strong bass and high efficiency
- 1 x 25 mm tweeter with neodymium magnet system and star-shaped cooling attachment on the terminal, provide a transparent sound image
- gold-plated mono binding posts with transparent screw-type terminal are easy to access and allow for larger cable



Finishes: graphite maple, cherry, silver

Specifications	ELAC BS 52	Crossover Frequency	3000 Hz
Dimensions HxWxD	250 x 150 x 172/160 mm	Nominal / Peak Power Handling	40 W / 60 W
Weight	approx. 3 kg	Frequency Range	60-23000 Hz
Type	2-way, closed	Sensitivity	87 dB/2.8V/m
Woofer	1 x 130 mm cone	Nominal Impedance	6 ohms
Tweeter	1 x 25 mm dome	Minimum Impedance	5.0 ohms at 230 Hz
Rec. Amplifier Power at Nominal Impedance	20 – 100 W/channel		

BS 52

Product Information

FINEST GERMAN ENGINEERING
ELAC

