

BS 52.2

ELAC
FINEST GERMAN ENGINEERING



The BS 52.2 Satellite Speaker.
Now available in white.



BS 52.2

Features

- The BS 52.2 is the perfect rear speaker in a home theatre setup with a trouble-free impedance of 6 Ohms, making it ideal for even lower powered amplifiers.
- No high-pass filter means the speaker receives the full spectrum of music, making it sound more mature than many satellite speakers.
- Closed box design. This makes the speaker ideal for wall mounting using the built in mounting fixing.
- Seamless, elegant design, now available in a brand new satin white finish.
- Colour co-ordinated metal grille.

Specification

Dimensions (inc. grille)	210 × 136 × 165 mm (H × W × D)
Weight	2.3kg
Principle	2 way, closed box
Woofer	110 mm cone
Tweeter	25 mm silk dome
Crossover frequency	2,500 Hz
Nominal power handling	40W
Peak power handling	60W
Frequency range (as IEC 268-5)	65Hz – 25,000Hz
Sensitivity	83dB/W/m
Sensitivity	84dB for 2.83V at 1m
Amplifier suitability	4 – 8Ω
Nominal impedance	6Ω
Minimum impedance	4.8Ω at 240 Hz
Recommended amplifier power	20 – 100W per channel (at nominal impedance)
Available finishes	Satin white. Also available in black ash and dark cherry

The BS 52.2 is the smallest member of the 50.2 Series.



ELAC Electroacoustic GmbH
Rendsburger Landstrasse
215-241 13 Kiel
Germany

www.elac.com

Dealer Details: