

BS 62.2

ELAC
FINEST GERMAN ENGINEERING



The BS 62.2 Satellite Speaker.
It sounds as good as it looks.

BS 62.2

Features

- Modern, high-grade sound.
- Special faceplate construction means there are no visible screws on the front of the speaker - only the tweeter and the woofer diaphragm are visible.
- Cloth grille fixed by magnets - no visible pins, or catches.
- Faceplate in Black High Gloss Finish Cabinet either in Black Ash or in Dark Walnut Finish
- Bass reflex plugs and hemispherical self-adhesive silicone-rubber feet included



Specification

Dimensions (inc. grille)	260mm x 160mm x 262mm (H x W x D)
Weight	4.5kg
Principle	2 way bass reflex
Woofer	135mm Ø AS cone
Tweeter	25mm dome
Crossover filter frequency	2300 Hz
Nominal power handling	50W
Peak power handling	70W
Frequency range (IEC 268-5)	48Hz – 25000Hz
Sensitivity	86.5dB for 2.83V at 1m
Amplifier suitability	4 – 8Ω
Nominal impedance	6Ω
Minimum impedance	4.6Ω / 260Hz
Recommended amplifier power	20 – 120W per channel (at nominal impedance)
Available finishes	Black ash or dark walnut with black gloss faceplate

ELAC Electroacoustic GmbH
Rendsburger Landstrasse
215-24113 Kiel
Germany

www.elac.com

Dealer Details: