

Strong, reliable, great sound: FS 58



The new top model of the 50 series offers strong bass sound and a midrange of high resolution. The slender FS 58 combines an elegant design with breathtaking sound for all applications from stereo to home cinema, hi-fi to surround sound.

Technical features

- 2 x 175 mm high-power woofer for balanced sound and high efficiency with cellulose diaphragm and concave-shaved dome, capton bobbin and ferrite ring for good power handling
- 1 x 130 mm powerful midrange driver for high resolution of the midrange area
- 1 x 25 mm tweeter with neodymium magnet system and star-shaped cooling attachment on the terminal
- two separate crossover net-works for the woofer/ midrange/ tweeter area
- gold-plated bi-wiring binding posts with transparent screw-type terminal and gold-plated, isolated cable suspension bridges
- overload-protection provides trouble free operation: this loudspeaker is recommended for use with 20-100W/ch powerful amplifiers

- the bass port's double flare design minimises air noise and friction losses
- elegant design: all driver baskets and mounting plates of the 50 series are in the new colour *titan metallic*, specially designed for ELAC
- robust base with spikes for decoupling and for improved stability

Finishes: graphite maple, cherry, silver



Specifications	ELAC FS 58	Crossover Frequency	720/2550 Hz
Dimensions H x W x D	1055 x 250 x 300/285 mm	Nominal Peak Power Handling	100 W / 140 W
Weight	approx. 20 kg	Frequency Range	40-23000 Hz
Type	3 way, bass reflex	Sensitivity	90 dB/2.8V/m
Woofer	2 x 175 mm cone	Nominal Impedance	4 ohms
Midrange	1 x 130 mm cone	Minimum Impedance	3.0 ohms at 130 Hz
Tweeter	1 x 25 mm dome		
Recom. Amplifier Power at Nominal Impedance	20 – 180 W/channel		